



C+P fire-protected cabinet Certos, 1950x650x500mm, 7035/7016

Fire-protected cabinet Certos, Body and doors made of sturdy steel construction with high-quality enamel coating, double-walled on all sides and insulated with 25 mm thick class A1 special insulating plates, non-combustible in accordance with DIN 4102, door mounted on bolt hinges at the top and bottom, generous opening angle of approx. 180 degrees, increased burglar-proof design thanks to sturdy door locks that engage in the side walls on the left and right, locking mechanism with 5 bolts (3x at the side, 1x at the top/bottom), 1 Robust cabinet handle, color: black, 4 Varnished steel shelves, with a high load capacity of 70 kg, 1 Double-bit safety lock with 2 keys, Dimensions (H x W x D): 1950 x 650 x 500 mm, Colour: RAL 7035 Light grey, Doors: RAL 7016 Anthracite grey, Interior fitting: RAL 7035 Light grey, Interior fitting: RAL 7035 Light grey

Product advantages:

- + Double-walled, insulated steelfronts for high stability and pleasant noise behavior
- + Door opening angle 180° for easy and convenient access to the cabinet contents
- + High load capacity of the shelves of 70 kg for flexible use
- + High flexibility of interior fitting due to adjustability in 15 mm increments
- + Class A1 insulating panels in accordance with DIN 4102 between the walls of the double-walled cabinet, to protect against light fires
- + 5-fold bolt lock system (3 x at the side, 1 x each at the top and bottom) for secure lock and protection against easy break-in attempts



Front color: RAL 7016 anthracite gray

Depth: 500

lock: cylinder lock

Body color: RAL 7035 light gray

Load capacity shelves: 70

Height: 1950

Door opening angle: 180

Opening dimensions door (height):
1812

Opening dimensions door (width):
550

Weight: 94.79

Inner depth: 455

Total internal height: 1790

Guarantee: 10

Width: 650

Inner width other: 646

€1,577.00*

*List price excl. VAT plus shipping costs

C + P GmbH & Co. KG
GmbH & Co. KG
Boxbachstraße 1
35236 Breidenbach
USt.-ID: DE 183061659

Contact:
Telephone: +49 6465 919-0
Fax: +49 6465 919-200
Email: sales@cp.de

Terms and Conditions / Legal Notice / Privacy Policy





Many of our products are GS-tested by TÜV Thüringen. We will be happy to send you copies of the relevant certificates on request.

