Datasheet "049000-10|S10001"

C+P lockers, Evolo PLUS, 1 compartment, 1850x300x500mm, 7035/1023

locker Evolo PLUS, 1 compartment, compartment width 300 mm, sturdy steel construction body with high-quality enamel coating for high UV and corrosion resistance, particularly burglar-proof **Depth:** 500 construction in accordance with level C as per DIN 4547, with rear louvered openings at the top and bottom, 1 storage shelf inside, 1 sturdy changing room rail made of oval profile with 3 antirotation double sliding hooks incl. system holder underneath, With floor gliders for practical cabinet and floor protection, Door opening limiter 90 degrees, as protection against overstretching the door, Door(s) hinged on the right, Steel door(s) with soft stop and closed side profiles for maximum stability, with easy-to-clean ventilation hole pattern at the top and bottom, mounting in sturdy bolt hinges, 1 Ergonomic safety turning bolt for padlocks with bolt size 6 to 8 mm, incl. door protection, 1 Plastic label holder, black, self-adhesive, incl. transparent plastic cover and white label for individual labeling, Dimensions (H x W x D): 1850 x 300 x 500 mm, Color: RAL 7035 Light grey, Doors: RAL 1023 Traffic yellow

Product advantages:

- + Body with ventilation openings at the top and bottom for optimum air circulation
- + Doors extremely torsion resistant due to closed side profiles
- + Fronts additionally with easy-to-clean ventilation hole pattern for even more effective ventilation
- + Door opening limiter to protect the door from overstretching and from overlapping with the usable space of the neighboring cabinet
- + Increased corrosion protection thanks to zinc-plated locker base and aluminum floor gliders
- + Level adjustment for easy compensation of uneven floors
- + Safety turning bolt latch for padlock, ergonomically shaped, turns when closed and thus prevents breaking open by over-turning
- + Particularly burglar-resistant construction in accordance with level C of DIN 4547

Substructure: Floor glider

lock: Safety turning bolt Door opening angle: 90 Total internal height: 1787 Body color: RAL 7035 light gray

Height: 1850 **Width: 300**

Number of compartments: 1 Front color: RAL 1023 Traffic yellow

Inner depth: 477

Opening dimensions door (height):

1749

Weight: 21.4

Inner width other: 298

Opening dimensions door (width):

240

Guarantee: 10



*List price excl. VAT plus shipping costs

C + P Möbelsysteme GmbH & Co. KG Boxbachstraße 1

Contact:

Telephone: +49 6465 919-0 Fax: +49 6465 919-200 Email: sales@cp.de

35236 Breidenbach USt.-ID: DE 183061659

German Quality" from the market leader

The color concept

With our new color concept, we are not only presenting current and attractive colors for every environment, but have also greatly simplified the color surcharge system. You won't need it very often anyway, because we now offer 144 colors and color combinations at no extra charge.

Locking systems

One for everything? That was once the case. Today's locking system solutions from C+P are as diverse as the applications for which they are designed. We would be happy to advise you on the options available for your specific project.

Accessories

Want to get the most out of your locker or steel cabinet for your practice? C + P offers a wide range of additional equipment.

Trust is good, but ...

control is better. At least when it comes to quality assurance. That is precisely why both our manufacturing processes and the C+P products themselves are subject to extremely demanding quality management, which is essentially based on two column bases: our in-house test laboratory on the one hand and, of course, regular external inspections and controls on the other.

DMSZ zertifiziert nach ISO 9001

DMSZ zertifiziert nach ISO 50001 DMSZ
zertifiziert nach
ISO 14001

UM 00945

DMSZ zertifiziert nach ISO 9001



Many of our products are GS-tested by TÜV Thüringen. We will be happy to send you copies of the relevant certificates on request.





C + P Möbelsysteme GmbH & Co. KG Boxbachstraße 1 35236 Breidenbach USt.-ID: DE 183061659 Contact:

Telephone: +49 6465 919-0 Fax: +49 6465 919-200 Email: sales@cp.de

