Datasheet "049020-10|S10017"

C+P Spind mit Sockel, Evolo PLUS

Spind Evolo PLUS, 1 Abteil, Abteilbreite 300 mm, Korpus aus stabiler Stahlkonstruktion mit hochwertiger Einbrennbeschichtung für hohe UV- und Korrosionsbeständigkeit, besonders aufbruchgeschützte Konstruktion gemäß Stufe C nach DIN 4547, mit hinteren Belüftungsöffnungen oben und unten, innen 1 Ablageboden, darunter 1 stabile Garderobenstange aus Ovalprofil mit 3 verdrehsicheren Doppel-Schiebehaken inkl. Systemaufnahme, auf 100 mm hohem Sockel aus Kunststoff für erweiterten Korrosionsschutz sowie für leichte Bodenreinigung und saubere Optik, Türöffnungsbegrenzer 90 Grad, als Schutz vor Überdehnen der Tür, Tür(en) rechts angeschlagen, Stahl-Tür(en) mit Soft-Anschlag und geschlossenen Seitenprofilen für höchste Stabilität, mit reinigungsfreundlichem Belüftungslochbild oben und unten, Aufhängung in stabilen Drehbolzen, 1 Ergonomischer Sicherheits-Drehriegel für Vorhangschloss mit Bügelstärke 6 bis 8 mm, inkl. Tür-Schutz, 1 Kunststoff-Etikettenrahmen, schwarz, selbstklebend, inkl. Klarsichtkunststoff-Abdeckung und weißem Etikett zur individuellen Beschriftung, Maße (H x B x T): 1950 x 300 x 500 mm, Korpus: RAL 7016 Anthrazitgrau, Türen: RAL 7035 Lichtgrau, Sockel: RAL 7021 Schwarzgrau

Produktvorteile:

+ Korpus mit Lüftungsöffnungen oben und unten für optimale Luftzirkulation
+ Türen extrem verwindungssteif durch geschlossene Seitenprofile
+ Fronten zusätzlich mit reinigungsfreundlichem Belüftungslochbild für noch effektivere Belüftung
+ Türöffnungsbegrenzer zum Schutz vor Überdehnung der Tür und vor Überschneidung mit Nutzfläche des Nachbarschrankes
+ Erhöhter Korrosionsschutz durch verzinkten Spindboden und stabilen Kunststoff-Sockel
+ Niveauregulierung zum einfachen Ausgleich von Bodenunebenheiten
+ Sicherheits-Drehriegelverschluss für Vorhängeschloss, ergonomisch geformt, dreht in geschlossenem Zustand durch und verhindert damit das Aufbrechen durch Überdrehen
+ Besonders aufbruchgeschützte Konstruktion gemäß Stufe C nach DIN 4547



Tipping dimension: 2013

compartment width: 300

Body ventilation: Perforated strip in the wardrobe base/head unit

Substructure: Base

Adjustment travel level adjustment: 25

Body surface: varnished

Depth: 500

Front color: RAL 7035 light gray

lock: Safety turning bolt

Substructure material: Made of plastic

changing room rail: fixed

for bolt size: 6-8

Door opening angle: 90

Country of origin: EN

Door material: Steel

Profile changing room rails: oval

Labeling material: Made of plastic

Total internal height: 1787

Mounting front: bolt hinge

Attachment Labeling: self-adhesive

delivery condition: mounted

Height: 1950

Substructure height: 100

Checkroom height: 1325

C + P GmbH & Co. KG
Niederlassung Breidenbach
Boxbachstraße 1
35236 Breidenbach
VAT ID: DE150325774

Contact:
Telephone: +49 6465 919-0
Email: sales@cp.de

Terms and Conditions / Legal Notice / Privacy Policy

„German Quality"
from the market leader

Datasheet "049020-10|S10017"

C+P Spind mit Sockel, Evolo PLUS

GS tested safety: GS_TUV_Thueringen

Width: 300

key number: Bolt

Shipping method: by truck

front stop 2: Hinged on the right

Material clothes hooks: Made of plastic

Color base: RAL 7021 Black gray

Internal height of top compartment: 365

Door surface: varnished

Number of compartments: 1

Guarantee: 10 years

Body color: RAL 7016 anthracite gray

Front version: Hinged doors

labeling: label holder

Inner depth: 477

Material changing room rails: Made of plastic

door opening limiter: Yes

Internal height of lower compartments: 1420

storage shelf: fixed

Number of clothes hooks/person: 3

Safety when setting off: Level C according to DIN 4547

Number of storage shelves: 1

Brand: Evolo PLUS

Opening dimensions door (height): 1749

Suitability for wall installation: Yes

series: Evolo PLUS

Inner width other: 298

Opening dimensions door (width): 240

Customs TariffNo_DE: 94031091

Weight: 21.8

€384.00*

*List price excl. VAT plus shipping costs

C + P GmbH & Co. KG
Niederlassung Breidenbach
Boxbachstraße 1
35236 Breidenbach
VAT ID: DE150325774

Contact:
Telephone: +49 6465 919-0
Email: sales@cp.de

Terms and Conditions / Legal Notice / Privacy Policy

„German Quality"
from the market leader

The color concept

With our new color concept, we are not only presenting current and attractive colors for every environment, but have also greatly simplified the color surcharge system. You won't need it very often anyway, because we now offer 144 colors and color combinations at no extra charge.

Locking systems

One for everything? That was once the case. Today's locking system solutions from C+P are as diverse as the applications for which they are designed. We would be happy to advise you on the options available for your specific project.

Accessories

Want to get the most out of your locker or steel cabinet for your practice? C + P offers a wide range of additional equipment.

Trust is good, but ...

control is better. At least when it comes to quality assurance. That is precisely why both our manufacturing processes and the C+P products themselves are subject to extremely demanding quality management, which is essentially based on two column bases: our in-house test laboratory on the one hand and, of course, regular external inspections and controls on the other.

DMSZ zertifiziert nach ISO 9001 QM 00945

DMSZ zertifiziert nach ISO 50001 EnM 00945

DMSZ zertifiziert nach ISO 14001 UM 00945

DMSZ zertifiziert nach ISO 9001 QM 00945

TÜV Thüringen GS geprüfte Sicherheit

Many of our products are GS-tested by TÜV Thüringen. We will be happy to send you copies of the relevant certificates on request.

Hessisches Präqualifikationsregister Zertifikat HPQR Auftragsberatungsstelle Hessen e.V.

SILVER | Top 15% ecovadis Sustainability Rating FEB 2024

C + P GmbH & Co. KG
Niederlassung Breidenbach
Boxbachstraße 1
35236 Breidenbach
VAT ID: DE150325774

Contact:
Telephone: +49 6465 919-0
Email: sales@cp.de

„German Quality" from the market leader