



C+P PSA locker to separate work- and streetwear, Evolo PLUS, frames, 2 compartments, 2120x600x500mm, 7035/0010

PSA Lockers to separate work- and streetwear Evolo PLUS, 2 compartments for 1 person, for separate storage of personal and work clothing, compartment widths 300 mm, sturdy steel construction body with high-quality enamel coating for high UV and corrosion resistance, with rear ventilation openings at the top and bottom, inside 1 full-length storage shelf for extra-large PPE case, 1 changing room rail made of oval profile with 3 twistable double sliding hooks incl. system mount for each compartment. System holder, doors closing in the middle for joint lock, with frames made of sturdy square steel tube 30 x 30 mm, with adjustable floor gliders for easy level adjustment, Steel doors with soft stop and closed side profiles for maximum stability, with easy-to-clean ventilation hole pattern at the top and bottom, mounting in sturdy bolt hinges, Door opening limiter 90 degrees, as protection against overstretching the door, 1 Cylinder lock with 2 keys, locking circuit up to 1000 different key numbers, 2 Plastic label holder, black, self-adhesive, incl. transparent plastic cover and white label for individual labeling, Dimensions (H x W x D): 2120 x 600 x 500 mm, Color: RAL 7035 Light grey, Doors: 2406015 RDS Architectural blue, Frame: RAL 7021 Black grey

Product advantages:

- + Safe and convenient separation of private and work clothing in accordance with ASR (workplace guidelines)
- + Body with ventilation openings at the top and bottom for optimum air circulation
- + Doors hinged together for a common lock
- + Doors extremely torsion resistant due to closed side profiles
- + Fronts additionally with easy-to-clean ventilation hole pattern for even more effective ventilation
- + Door opening limiter to protect the door from overstretching and from overlapping with the usable space of the neighboring cabinet
- + Level adjustment for easy compensation of uneven floors
- + Full-length storage shelves per double compartment for extra-large PPE case
- + Particularly burglar-resistant construction in accordance with level C of DIN 4547



Front color: RAL 2406015

Architectural blue

Depth: 500

Opening dimensions door (height):
1599

Door opening angle: 90

lock: cylinder lock

Substructure: frame

Body color: RAL 7035 light gray

Number of compartments: 2

Height: 2120

Width: 300

Inner depth: 477

Total internal height: 1637

Inner width other: 298

Opening dimensions door (width):
240

Guarantee: 10

Weight: 39.2

€619.00*

*List price excl. VAT plus shipping costs

C + P GmbH & Co. KG
GmbH & Co. KG
Boxbachstraße 1
35236 Breidenbach
USt.-ID: DE 183061659

Contact:
Telephone: +49 6465 919-0
Fax: +49 6465 919-200
Email: sales@cp.de

[Terms and Conditions](#) / [Legal Notice](#) / [Privacy Policy](#)



The color concept

With our new color concept, we are not only presenting current and attractive colors for every environment, but have also greatly simplified the color surcharge system. You won't need it very often anyway, because we now offer 144 colors and color combinations at no extra charge.

Locking systems

One for everything? That was once the case. Today's locking system solutions from C+P are as diverse as the applications for which they are designed. We would be happy to advise you on the options available for your specific project.

Accessories

Want to get the most out of your locker or steel cabinet for your practice? C + P offers a wide range of additional equipment.

Trust is good, but ...

control is better. At least when it comes to quality assurance. That is precisely why both our manufacturing processes and the C+P products themselves are subject to extremely demanding quality management, which is essentially based on two column bases: our in-house test laboratory on the one hand and, of course, regular external inspections and controls on the other.



Many of our products are GS-tested by TÜV Thüringen. We will be happy to send you copies of the relevant certificates on request.

