



C+P firemen's lockers, Kombi, 1 compartment, 1850x800x500mm, 3000/3000

Firemen's locker Kombi, 2 compartments for 1 person for separate storage of work and private clothing in accordance with DIN 14092 / DGUV, compartment width per person left 400 mm + right 400 mm, body made of sturdy steel structure with high-quality enamel coating for high UV and corrosion resistance, bottom electrolytically galvanized, with rear ventilation openings at top and bottom, inside right 2 compartments, below 2 storage shelves, below 1 sturdy room rail made of oval profile with 4 twist-proof double sliding hooks incl. system holder, 1 Helmet base, shortened, for kink-free positioning of the neck guard, 1 Multifunctional hook rails on the side, each with 3 sliding stainless steel sliding hooks for safety belt, lifeline, etc., 1 Cylinder lock with 2 keys, locking circuit up to 1000 different key numbers, With floor gliders for practical cabinet and floor protection, Dimensions (H x W x D): 1850 x 800 x 500 mm, Colour: RAL 3000 Flame red, Doors: RAL 3000 Flame red

Product advantages:

- + Proper and convenient separation of work- and streetwear from private clothing
- + Body with ventilation openings at the top and bottom for optimum air circulation
- + Doors extremely torsion resistant due to closed side profiles
- + Fronts additionally with easy-to-clean ventilation hole pattern for even more effective ventilation



Door opening angle: 110
Security compartments height: 203
Helmet bottom: shortened
Adjustment travel level adjustment: 25
Body surface: varnished
Depth: 500
Key type: Beard key
hook rail: fixed
Material hooks (hook rails): Stainless steel
changing room rail: fixed
Internal height of lower compartments: 1421
Country of origin: EN
Door material: Steel
Profile changing room rails: oval
lock: cylinder lock
Front fitting: inside
Substructure surface: varnished
Closing circuit: up to 1000
Helmet holder material: Made of plastic
Total internal height: 1787
Mounting front: bolt hinge
Profile hook rails: oval
delivery condition: mounted
Number of keys: 2



C+P firemen's lockers, Kombi, 1
compartment, 1850x800x500mm,
3000/3000

Substructure height: 100
level adjustment: Yes
front stop type: folding in
Height: 1850
key number: Bolt
front stop: DIN right
Shipping method: by truck
front stop 2: Hinged on the right
Material clothes hooks: Made of plastic
insertion slot: Yes
Color base: RAL 7021 Black gray
Front ventilation: Ventilation hole pattern
Internal height of top compartment: 365
Door surface: varnished
Brand: Kombi
Guarantee: 10 years
Security compartments depth: 477
Opening dimensions door (height): 154
Attachment Labeling: imprinted
Material hook rails: Made of plastic
Material changing room rails: Made of plastic
series: Kombi
Number of doors: 1
Number of hooks/hook rails: 3

€568.00*

*List price excl. VAT plus shipping costs

The color concept

With our new color concept, we are not only presenting current and attractive colors for every environment, but have also greatly simplified the color surcharge system. You won't need it very often anyway, because we now offer 144 colors and color combinations at no extra charge.

Locking systems

One for everything? That was once the case. Today's locking system solutions from C+P are as diverse as the applications for which they are designed. We would be happy to advise you on the options available for your specific project.

Accessories

Want to get the most out of your locker or steel cabinet for your practice? C + P offers a wide range of additional equipment.

Trust is good, but ...

control is better. At least when it comes to quality assurance. That is precisely why both our manufacturing processes and the C+P products themselves are subject to extremely demanding quality management, which is essentially based on two column bases: our in-house test laboratory on the one hand and, of course, regular external inspections and controls on the other.



Many of our products are GS-tested by TÜV Thüringen. We will be happy to send you copies of the relevant certificates on request.

