



## C+P tool cabinet Acurado, 1950x500x400mm, 7016/7016

Tool cabinet Acurado, body made of sturdy steel construction with high-quality enamel coating for high UV resistance, with floor gliders as practical cabinet and floor protection, high flexibility of interior fitting thanks to height adjustability in 15 mm increments, door with acrylic glass viewing window for direct view, closed side profiles and concealed locking rods for maximum stability and burglar-proof design, with soft stop, door mounting bracket on external hinges with generous opening angle of approx. 180 degrees, 4 zinc-plated steel shelves with a high load capacity of 70 kg, 1 Ergo-Lock grip lock for optimum operation safety and wear resistance, 3-bolt cylinder locks, with cylinder lock and 2 keys, dimensions (H x W x D): 1950 x 500 x 400 mm, Color: RAL 7016 anthracite gray, Doors: RAL 7016 anthracite gray



**Body surface:** varnished  
**Key type:** Beard key  
**Door material:** Steel  
**lock:** cylinder lock  
**Mounting front:** bolt hinge  
**Load capacity shelves:** 70  
**Number of keys:** 2  
**Height:** 1950  
**GS tested safety:**  
GS\_TUV\_Thuringen  
**front stop type:** folding in  
**series:** Acurado 89  
**Guarantee:** 10 years  
**Front version:** Hinged doors  
**Door opening angle:** 180  
**handle:** Ergo-Lock recessed grip  
**Optics doors:** Acrylic glass viewing window  
**Height-adjustable base:** Yes  
**Floor height adjustment grid:** 15  
**delivery condition:** by truck  
**Shelves material:** Steel  
**key number:** 3-bar  
**Surface of shelves:** zinc-plated  
**Body material:** Steel  
**Width:** 502

**€618.00\***

\*List price excl. VAT plus shipping costs

C + P Möbelsysteme  
GmbH & Co. KG  
Boxbachstraße 1  
35236 Breidenbach  
USt.-ID: DE 183061659

Contact:  
Telephone: +49 6465 919-0  
Fax: +49 6465 919-200  
Email: sales@cp.de

Terms and Conditions / Legal Notice / Privacy Policy





Many of our products are GS-tested by TÜV Thüringen. We will be happy to send you copies of the relevant certificates on request.

